metallux

LINEAR AND ROTARY SENSORS

Precise.
Robust.
Reliable.



Portfolio
Linear sensors

Potentiometer Element



Element

Membrane sensors



MTP-L



MTP-LX



MMP

Potentiometers



WPL-LH



WPL-0S

General data	Sensor technology	**Potentiometric**	**Potentiometric**	**Potentiometric**	**Potentiometric**	**Potentiometric**	**Potentiometric**
	Type of contact	Wiper	Spring loaded pin	Spring loaded pin	Non-contact, magnetic	Wiper	Wiper
	Sensor type	Absolute measuring	Absolute measuring	Absolute measuring	Absolute measuring	Absolute measuring	Absolute measuring
	Curcuit	As voltage divider	As voltage divider	As voltage divider	As voltage divider	As voltage divider	As voltage divider
Electrical data	Measuring range, adjustable	20 – 500 mm	30 – 500 mm	50 – 500 mm	50 – 500 mm	25 – 300 mm	30 – 300 mm
	Output signal	Analog	Analog	Analog	Analog	Analog	Analog
	Independent linearity	± 2 %, ± 0.25 % optional	± 2 %	± 0.3 %	± 2 %	± 1 %	± 2 %, ± 0.25 % optional
	Resolution*	approx. 10 µm	0.05 mm achievable	0.05 mm achievable	0.1 mm achievable	0.05 mm achievable	0.05 mm achievable
	Resistance range	5 kΩ, 10 kΩ	2,5 kΩ per 100 mm travel	4 kΩ per 100 mm travel	2.5 kΩ per 100 mm travel	Standard 10 kΩ, 5 kΩ possible	5 kΩ, 10 kΩ
	Resistance tolerance	± 20 %	± 30 %	± 30 %	± 30 %	± 20 %	± 20 %
	Max. wiper current	5 mA in case of malfunction	5 mA in case of malfunction	5 mA in case of malfunction	5 mA in case of malfunction	5 mA in case of malfunction	5 mA in case of malfunction
	Supply voltage	5 VDC typ., 3 to 30 VDC possible	5 VDC typ., 3 to 30 VDC possible	5 VDC typ., 3 to 30 VDC possible	5 VDC typ., 3 to 30 VDC possible	5 VDC typ., 3 to 30 VDC possible	5 VDC typ., 3 to 30 VDC possible
Mechanical data	Sensor thickness	1.5 mm	0.8 mm	1.8 mm	< 2 mm	16 mm	5.5 x 17 mm
	Travel speed	> 2 m/sec	1 m/sec	1 m/sec	≤ 3 m/sec	2 m/sec	2 m/sec
	Lifespan in cycles	Up to 50 M	> 5 M	> 25 M	50 M	Up to 5 M	10 M
	Mounting	Self-adhesive	Self-adhesive	Self-adhesive	Self-adhesive	Screw, clamp	Glue
Environmental data	Operating temperature	-40 °C to +125 °C	-25 °C to +85 °C	-25 °C to +105 °C	-10 °C to +70 °C	-25 °C to +65 °C	-25 °C to +85 °C
	Protection class acc. to IEC 60529	–	IP 65**	IP 67**	IP 65**	IP 63	–
	EMC/ESD	Uncritical	Uncritical	Uncritical	Uncritical	Uncritical	Uncritical
Electrical connection	Solder pad	•	•	•	•		•
	Cable					•	
	Connector		•	•	•		
	Crimp		•	•	•		

*Resolution analog: limited by evaluation unit

**Except for electrical connection and connector

For more information about the products, please refer to the respective product data sheet.

Portfolio
Rotary sensors

		Potentiometer Element	Membrane sensors		Potentiometers			
								
		Element	MTP-R	MTP-RX	HMS 220	POH 120	POH 120	
General data	Sensor technology	**Potentiometric**	**Potentiometric**	**Potentiometric**	**Hall**	**Hall**	**Hall**	
	Type of contact	Wiper	Spring loaded pin	Spring loaded pin	Magnet	Magnet	Magnet	
	Sensor type	Absolute measuring	Absolute measuring	Absolute measuring	Absolute measuring	Absolute measuring	Absolute measuring	
	Curcuit	As voltage divider	As voltage divider	As voltage divider	–	–	–	
Electrical data	Measuring range, adjustable	0° – 355°	25° – 345°	25° – 345°	0° – 360°, programmable	0° – 360°, programmable	0° – 360°, programmable	
	Output signal	Analog, 0 to 100 % of supply voltage	Analog, 0 to 100 % of supply voltage	Analog, 0 to 100 % of supply voltage	Analog, 10 to 90 % of supply voltage	Analog, 10 to 90 % of supply voltage	Analog, 10 to 90 % of supply voltage	
	Independent linearity	± 2 %, optional ± 0.25 %	± 2 %	± 2 %, optional ± 0.3 %	± 0.5 %	± 0.5 %	± 0.5 %	
	Resolution*	Analog	Analog	Analog, 0.05 mm achievable	Analog 12 bit, SPI 14 bit, PWM 14 bit	12 bit, <0.1°	12 bit, <0.1°	
	Resistance range	5 kΩ, 10 kΩ	2.5 kΩ per 25 mm circumference	Depending on component size	–	–	–	
	Resistance tolerance	± 20 %	± 30 %	± 30 %	–	–	–	
	Max. wiper current	5 mA in case of malfunction	5 mA in case of malfunction	5 mA in case of malfunction	11 mA	11 mA	11 mA	
	Supply voltage	5 VDC typ., 3 to 30 VDC possible	5 VDC typ., 3 to 30 VDC possible	5 VDC typ., 3 to 30 VDC possible	5 VDC ± 10 %	5 VDC ± 10 %	5 VDC ± 10 %	
Mechanical data	Sensor thickness	1.5 mm	0.8 mm	0.8 mm	–	–	–	
	Housing Ø	–	–	–	22.2 mm	13 mm	13 mm	
	Shaft length / Ø	–	–	–	6.7 mm, Ø 6 mm	15.5 mm, Ø 3 mm	7 mm, Ø 3 mm	
	Travel speed	2 m/sec	1 m/sec	1 m/sec	–	–	–	
	Lifespan in cycles	Up to 50 M	> 5 M	> 25 M	200 M	> 10 years	10 M	
	Bearing	–	–	–	Double ball bearing	Decoupled	Plain bearing	
	Mechanical coupling	–	–	–	Shaft	Shaft	Shaft	
	Mounting	Self-adhesive / screw	Self-adhesive	Self-adhesive	Thread	Servo flange	Servo flange	
Environmental data	Operating temperature	-40 °C to +125 °C	-25 °C to +85 °C	-25 °C to +85 °C / 105 °C	-40 °C to +105 °C	-40 °C to +85 °C	-40 °C to +85 °C	
	Protection class acc. to IEC 60529	–	IP 65**	IP 65**	IP 65	IP 65	IP 65	
	EMC/ESD	Uncritical	Uncritical	Uncritical	–	–	–	
Electrical connection	Solder pad	•						
	Cable	•	•	•	•	•	•	
	Connector	•	•	•				
	Crimp		•	•				

*Resolution analog: limited by evaluation unit

**Except for electrical connection and connector

For more information about the products, please refer to the respective product data sheet.

Portfolio
Rotary sensors

Potentiometers









		HWL 60	PGL 60	POL 120	POL 200	POL 220	POL 230	POL 790
General data	Sensor technology	**Potentiometric**	**Potentiometric**	**Potentiometric**	**Potentiometric**	**Potentiometric**	**Potentiometric**	**Potentiometric**
	Type of contact	Wiper	Wiper	Wiper	Wiper	Wiper	Wiper	Wiper
	Sensor type	Absolute measuring	Absolute measuring	Absolute measuring	Absolute measuring	Absolute measuring	Absolute measuring	Absolute measuring
	Curcuit	As voltage divider	As voltage divider	As voltage divider	As voltage divider	As voltage divider	As voltage divider	As voltage divider
Electrical data	Measuring range, adjustable	320°	320°	308°	320°	320°	340°	350°
	Output signal	Analog, 0 to 100 % of supply voltage	Analog, 0 to 100 % of supply voltage	Analog, 0 to 100 % of supply voltage	Analog, 0 to 100 % of supply voltage	Analog, 0 to 100 % of supply voltage	Analog, 0 to 100 % of supply voltage	Analog, 0 to 100 % of supply voltage
	Independent linearity	± 2 %	± 2 %	± 2.5 %	± 2 %	± 2 %	± 2 %	± 2 %
	Resolution*	Analog	Analog	Analog	Analog	Analog	Analog	Analog
	Resistance range	10 kΩ	10 kΩ	10 kΩ	10 kΩ	5 kΩ	5 kΩ	5 kΩ, 10 kΩ
	Resistance tolerance	± 20 %	± 20 %	± 20 %	± 20 %	± 20 %	± 20 %	± 20 %
	Max. wiper current	5 mA in case of malfunction	5 mA in case of malfunction	5 mA in case of malfunction	5 mA in case of malfunction	5 mA in case of malfunction	5 mA in case of malfunction	5 mA in case of malfunction
	Supply voltage	5 VDC typ., 3 to 30 VDC possible	5 VDC typ., 3 to 30 VDC possible	5 VDC typ., 3 to 30 VDC possible	5 VDC typ., 3 to 30 VDC possible	5 VDC typ., 3 to 30 VDC possible	5 VDC typ., 3 to 30 VDC possible	5 VDC typ., 3 to 30 VDC possible
Mechanical data	Sensor thickness	10 mm	17.6 mm	–	–	–	–	–
	Housing Ø	30 x 32 mm	31 mm	13 mm	20 mm	22.2 mm	22.2 mm	79 mm
	Shaft length / Ø	Hollow shaft Ø 6 mm	Hollow shaft Ø 6 mm	7 mm / Ø 3 mm	13 mm / Ø 6 mm	15 mm / Ø 6 mm	10 mm / Ø 3.165 mm	13 mm / Ø 8 mm
	Travel speed	–	–	–	–	–	–	–
	Lifespan in cycles	3 M	25 M	3 M	1 M	10 M	20 M	10 M
	Bearing	Floating plain bearing	Ball bearing	Plain bearing	Plain bearing	Plain bearing	Ball bearing	Plain bearing
	Mechanical coupling	Hollow shaft	Hollow shaft	Shaft	Shaft	Shaft	Shaft	Shaft or rotary disk
	Mounting	Stick	Thread	Servo flange	Thread	Thread	Servo flange	Screw
Environmental data	Operating temperature	-25 °C to +85 °C	-25 °C to +85 °C	-25 °C to +85 °C	-25 °C to +85 °C	-25 °C to +85 °C	-25 °C to +85 °C	-25 °C to +85 °C
	Protection class acc. to IEC 60529	IP 50	IP 63	IP 65	IP 50	IP 65	IP 63	IP 67
	EMC/ESD	Uncritical	Uncritical	Uncritical	Uncritical	Uncritical	Uncritical	Uncritical
Electrical connection	Solder pad	•			•	•	•	
	Cable	•	•	•	•	•	•	
	Connector							•

*Resolution analog: limited by evaluation unit

For more information about the products, please refer to the respective product data sheet.